







DIGIXBEE INDUSTRIAL GATEWAY

Programmable gateway connects Digi XBee enabled devices to remote applications over cellular or Ethernet

Digi XBee® Industrial Gateway is a rugged Digi XBee to IP solution. Ideal for any environment, the gateway has an extended temperature range and rugged enclosure.

Digi XBee Industrial Gateway features scalable remote configuration and management of Digi XBee networks. By default, all Digi XBee data sent to the gateway is automatically available to online applications via Digi Remote Manager® (Digi RM). With a simple, opensource Python development environment, this gateway also enables custom applications to run locally while

interfacing across existing Ethernet or cellular networks for WAN connectivity to cloud-based apps.

Gain critical insights into your deployed devices and manage your network with Digi RM — the command center for your deployment. Digi RM is a cloud-based solution that facilitates easy setup, mass configuration, maintenance and support for hundreds or even thousands of remote Digi devices. Digi Remote Manager lets you evaluate, update and configure your Digi enterprise products — and the health of your network — at scale after deployment.

BENEFITS

- Open-source Python environment for custom application development on the gateway
- Out-of-box integration with **Digi Remote Manager** enables remote connectivity, configuration and management of Digi XBee networks
- ZigBee enabled for connection to local wireless devices
- Cellular and Ethernet WAN options for flexible broadband connectivity
- Can be deployed in any environment due to industrial temp range and rugged enclosure

ZIGBEE® WIRELESS MESH NETWORK DIGI XBEE® INDUSTRIAL

APPLICATION EXAMPLE

RELATED PRODUCTS











SPECIFICATIONS	Digi XBee® Industrial Gateway	Digi XBee® Industrial Cellular Gateway	
GENERAL			
MANAGEMENT	Secure enterprise management via Digi Remote Manager®		
PROTOCOLS	UDP/TCP, DHCP		
LEDS	Cellular signal strength, network (LAN/WAN), Zigbee® (wireless LAN), power		
SECURITY	TLS 1.2, cellular network security		
WWAN			
3G HSPA+, BANDS	N/A	B5(850), B8(900), B2(1900), B1(2100), B4(AWS)	
LTE CATEGORY 1	N/A	Verizon: bands 2, 4, 13 AT&T, T-Mobile: B2(1900), B4(AWS1700), B5(850), B12/B12(700)	
ANTENNA CONNECTORS	N/A	HSPA+ version: $1 \times 50 \Omega$ SMA (center pin: female); LTE version: $2 \times 50 \Omega$ SMA (center pin: female)	
SIM SLOTS	N/A	2 x 2FF SIM slots; second SIM slot reserved for future use	
SIM SECURITY	N/A	Screw-down SIM cover	
SOFTWARE & MANAGEMENT			
PYTHON	2.7.1		
MEMORY FREE SPACE	20 MB RAM and 20MB Flash for Python applications		
XBEE GATEWAY APPLICATION	Wireless LAN data sent to the gateway is automatically available to online applications via Digi Remote Manager		
ZIGBEE		5	
ZIGBEE STACK	ZigBee Standard and ZigBee PRO versions available		
ZIGBEE MODULES SUPPORTED	XBee S1, XBee S 3		
ZIGBEE	Standard: transmit power 6.3 mW (+8 dBm); receiver sensitivity: -102 dBm PRO: transmit power 63 mW (18dBm): receiver sensitivity: -102 dBm		
ZIGBEE ANTENNA	1 x 50 Ω SMA (center pin: female)		
ETHERNET			
PORTS	(1) R I-45 port		
PHYSICAL LAYER	(1) RJ-45 port		
DATA RATE	10/100 Base-T		
MODE	10/100 Mbps (auto-sensing)		
		Full or half duplex (auto-sensing)	
INTERFACE	Auto MDI/MDIX		
ROUTING	Ethernet port designed for configuration and WAN backhau	l	
PHYSICAL			
DIMENSIONS (L X W X H)	7.62 cm x 10.16 cm x 2.54 cm (3 in x 4 in x 1 in)		
WEIGHT	.22 kg (0.5 lb)		
ENCLOSURE MATERIAL/RATING	Industrial (metal)/IP30		
POWER REQUIREMENTS			
POWER INPUT	5 VDC +/- 5%; Digi approved power supply must be used		
POWER SUPPLY	See accessory options		
POWER CONSUMPTION	Typical 1.2 W, Max 2.5 W	Typical 3.5 W; Max 11 W	
ENVIRONMENTAL			
OPERATING TEMPERATURE	-30° C to 70° C (-22° F to 158° F)	-30° C to 70° C (-22° F to 158° F) Reduced performance above 60° C (140° F)	
RELATIVE HUMIDITY	5% to 95% (non-condensing)		
APPROVALS			
GSM/UMTS	PTCRB, visit www.digi.com/resources/certifications for latest certifications		
CELLULAR CARRIERS	Verizon, AT&T, certified by most major international carriers		
SAFETY	IEC 60950-1:2005; EN 60950-1:2006; CSA C22.22 No. 60950-1		
EMISSIONS/IMMUNITY	FCC Part 15b, Industry Canada (IC), CE Mark		
WARRANTY			
PRODUCT WARRANTY	3-year*		

^{*}Standard 3-year warranty upgradeable to 5 years with purchase of a Digi Remote Manager Premier 5-year subscription applicable to the product purchased only at the time of product purchase and with product registration at that time in Digi Remote Manager.



DIGI REMOTE MANAGER®



Digi Remote Manager is the technology platform that brings networks to the next level, allowing networks — and the people who manage them — to work smarter. With Digi Remote Manager you can transform a multitude of dispersed IoT devices into a dynamic, intelligent network. Now you can easily deploy, monitor and diagnose thousands of mission-critical devices from a single point of command — on your desktop, tablet or phone. All the while, its software-defined security diligently safeguards your entire Digi ecosystem.

Learn more at www.digi.com/digi-remote-manager

CAPABILITIES

- Activate, monitor and diagnose your mission-critical devices from a single point of command and control — on your desktop or mobile app
- Schedule key operations including firmware updates and file management on a single device or on a group of devices, keeping your network functionality up-to-date and maintaining compliance standards
- Manage edge devices out-of-band via console terminal access
- Keep tabs on device health and connectivity across device deployments of any size
- Create detailed reports and enable real-time alerts for specified conditions
- Integrate device data through open APIs to gain deeper insights and control with third-party applications
- Report and alert on performance statistics, including connection history, signal quality, latency, data usage and packet loss

INFRASTRUCTURE

- Hosted in a commercial-grade cloud server environment that meets SOC 1°, SOC 2° and SOC 3° standards
- Superior availability, operating to 99.9% or greater
- Open APIs available to support application development

SECURITY

- More than 175 security controls in place to protect your data
- Member of the Center for Internet Security® (CIS®)
- Enables compliance with security frameworks like ISO27002, HIPAA, NIST and more
- Earned Skyhigh's CloudTrust™ Program highest rating of Enterprise-Ready

PART NUMBERS	DIGI XBEE® INDUSTRIAL GATEWAY
XGI-20CZ7-E00-W0	Digi XBee Industrial Gateway - ZigBee to Ethernet, power supply and antenna not included
XGI-2PCZ7-E00-W0	Digi XBee Industrial Gateway - ZigBee Pro to Ethernet, power supply and antenna not included
XGI-2PCZ7-EL1-W0	Digi XBee Industrial Gateway - ZigBee Pro to Cat 1, power supply and antenna not included

PART NUMBERS	ACCESSORIES
76000976	Kit, Digi TransPort 9-30 V DC/DC adapter
76002021	Power supply, 5 V barrel plug, wall plug in, commercial range
76000965	Kit, Digi TransPort WR11 XT power supply Int, industrial temperature range

PART NUMBERS	DIGI REMOTE MANAGER®
DIGI-RM-STD-1YR	Digi Remote Manager Standard - 1-year subscription
DIGI-RM-PRM-1YR	Digi Remote Manager Premier - 1-year subscription
DIGI-RM-PRM-3YR	Digi Remote Manager Premier - 3-year subscription
DIGI-RM-PRM-5YR	Digi Remote Manager Premier - 5-year subscription





© 1996-2021 Digi International Inc. All rights reserved. All trademarks are the property of their respective owners.



