



ADTRAN

1602-1

Standard RFoG Micronode



Benefits

- Simple, plug and play micronode solution for converting Radio Frequency signals at the customer premises
- Extends the life of existing Radio Frequency headend
- Provides a cost effective migration path for Cable Multiple System Operators fiber deployments
- Compact packaging for easy installation

Overview

Cable MSOs are deploying more fiber in their networks than ever before, but they face the challenge of executing this strategy in a cost effective manner. Minimizing upgrade cost and complexity by maintaining their headend and customer premises equipment are key factors to success.

The ADTRAN 1602-1 Radio Frequency over Glass (RFoG) micronode is the perfect solution for Cable MSOs who are making the transition to fiber, but are still looking to utilize the Radio Frequency (RF) signals generated by their current headend equipment. The ADTRAN 1602-1 provides a cost effective solution for converting these RF signals at the customer premises to useable signals that can traverse the legacy Coax wiring present in many homes.

Product Specifications

Optical Specifications Rx

- Distortion Performance (CNR), minimum: 48 dB
- Distortion Performance (CSO), maximum: 60 -dBc
- Distortion Performance (CTB), maximum: 65 -dBc
- Distortion Performance Note (CNR): 50–552 MHz CW Analog; 552–1002 MHz digital, -4 dBm receive
- Distortion Performance Note (CSO): 50–552 MHz CW Analog; 552–1002 MHz digital, 0 dBm receive
- Distortion Performance Note (CTB): 50–552 MHz CW Analog; 552–1002 MHz digital, 0 dBm receive
- Input Power, maximum: 0 dBm
- Input Power, minimum: -6 dBm
- LED Indicator, green: Optical input power
- Technology Type: Passive optical network (PON) compatible | RF over glass (RFoG)
- Wavelength, maximum: 1565.00 nm
- Wavelength, minimum: 1540.00 nm

RF Specifications Rx

- Operating Frequency Band: 54–1002 MHz
- Flatness: ± 2.0 dB
- Output Level, typical: 17 dBmV @ 550 MHz, 77 dB μ V @ 550 MHz
- Return Loss, minimum: 16 dB
- Tilt Across Frequency Band, typical: 5.00 dB

Optical Specifications Tx

- Laser Type: Distributed feedback (DFB) Class 1
- Technology Type: Passive optical network (PON) compatible | RF over glass (RFoG)
- Wavelength, nominal: 1610.00 nm
- Dynamic Range at NPR, minimum: 15 dB @ 30 dB
- Laser Activation Time: 1.0 μ s
- LED Indicator, green: Upstream RF activity
- Output Power, typical: 3 dBm

Product Specifications

Rf Specifications Tx

- Flatness: ± 1.5 dB
- Input Activation Level, typical: 14.000 dBmV | 74.000 dB μ V
- Input Power Range, typical: 20–45 dBmV | 80–105 dB μ V
- Operating Frequency Band: 5–42 MHz
- Return Loss, minimum: 16 dB

Electrical Specifications

- Electrical Safety Standard: CE | IEC 60825-1 | TÜV | US FCC Part 15B
- Power Consumption at Voltage, maximum: 2.5 W @ 12 Vdc

- Surge Capability Test Method: IEEE C62.41-A3 (6 kV, 200 A, Ring wave) on both ports
- Voltage Range: 8.5–18 Vdc

Environmental Specifications

- Operating Temperature: -40 °C to +65 °C (-40 °F to +149 °F)
- Relative Humidity: 5%–95%, non-condensing

Mechanical Specifications

- LED Indicator, green: dc input power
- Optical Port Interface: SC/APC Female
- RF Port Impedance: 75 ohm
- RF Port Interface: F Female

General Specifications

- Application: Indoor | Outdoor (enclosure required)
- Warranty: One year

Dimensions

- Height 24.64 mm | 0.97 in
- Length 105.41 mm | 4.15 in
- Net Weight 0.18 kg | 0.40 lb
- Width 89.66 mm | 3.53 in

Regulatory Compliance/Certifications

- ISO 9001:2008

Ordering Information

Hardware Options	Part No.
ADTRAN 1602 Standard Micronode, 1550/1610, 42/54 MHz, w/10G Filter and Power Inserter	17216021F1
Accessories	
External Power Supply (sold separately)	172PWR1

ADTRAN Pulse Supply
909 Ridgebrook Road., Sparks, Maryland 21152, USA
TEL : +1-410-583-1701 FAX : +1-410-583-1704



E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/adtran>

617216021F1-8A

December Copyright © 2016 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and Total Access are registered trademarks of ADTRAN, Inc. and its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense

ADTRAN
Certified
Supplier



TL9000
TL91270

ISO 9001
ISO 14001
TL 9000