

ADTRAN

6010-16

16-Port GPON OLT

SDX Series



Benefits

- Pay-as-you-grow, disaggregated 16-port GPON OLT
- Supports High-capacity, Open, Programmable Networks
- Supports Residential, Cloud and Enterprise Services
- Supports both IPTV and RF Overlay Video Service
- Offers front access ports
- Part of ADTRAN's Extensive and Growing Family of SD-Access Devices
- Supports Extended Range Optics (up to 62.5km) Enhancing Gigabit Service Reach
- Available in multiple airflow options.
- Supports Gigabit and Committed Information Rate (CIR) services
- Supports an extensive and growing family of ONTs
- Supports street cabinet deployment

Overview

ADTRAN Next-Generation PON OLTs are open, programmable and scalable access devices that support GPON access interfaces. These OLT access devices are part of ADTRAN's next-generation, data center optimized aggregation architecture that aligns with the forward-looking industry trend to build massively scalable and open systems.

Open, Programmable, Scalable

Being built around an open architecture, these OLTs can be aggregated by any high-density aggregation system, including ADTRAN's Nx100G next-generation aggregation switches. From a programmability perspective, these OLTs have open APIs that utilize standard NETCONF/YANG interfaces for all management functions, easing the integration into an SDN-controlled environment. For scalability, they are built around a "pay-as-you-grow" architecture where you simply add GPON/NGPON OLTs as needed without the upfront investment or system constraints of a big iron-chassis system. In addition to being open, programmable and scalable, all

embedded software functions in the OLT, ranging from ONT management, PON provisioning and IGMP processing, are virtualised and can be hosted on an external server to enable massive scalability and avoid the system constraints of embedded processing systems.

High-Performance with Flexibility

These OLTs offer non-blocking 80 Gbps uplink interfaces with embedded redundancy options to ensure that they can scale to support next-generation residential, business and backhaul services.

ADTRAN's GPON access device supports 16 SFP+ interfaces for 2.5/1.25G PON. This solution provides an ultra-flexible, high-capacity architecture with support for up to 128 ONTs per PON.

These OLTs offer all of the carrier-class features (i.e., ONT management, clocking, VLAN tag manipulation, resiliency, etc.) of a traditional chassis-based OLT system, but with much more flexibility, scalability, and an open architecture that cannot be matched by a closed, vendor-specific chassis system.



Front to Back Airflow Option



Side to Side Airflow Option

ADTRAN 6010-16

Product Specifications

Front Panel Interfaces

- 16 SFP+ Interfaces for GPON
- 2x QSFP+ Uplink Interfaces
- 4x SFP+ Uplink Interfaces

Performance

- Non-Blocking Uplink Capacity - up to 80Gbps using Link Aggregation (LAG)
- G.8032 ERPS ring support

Environment

- **Operating Temperature:** -40°F to 149°F (-40°C to 65°C)

Physical

- **Chassis:** 1U, 19-inch Rack Mountable Metal Enclosure
- **Dimensions:**
 - ◆ **S2S SKU**
 - Height: 1RU (1.72 inches, 4.37 centimeters)
 - Width: 17.22 inches (43.74 centimeters)
 - Depth: 9.28 inches (23.57 centimeters)
 - ◆ **F2B SKU**
 - Height: 1RU (1.72 inches, 4.37 centimeters)
 - Width: 17.22 inches (43.74 centimeters)
 - Depth: 12.15 inches (30.9 centimeters)
- **Power Supply:** -48VDC with redundant feed
- **Redundancy:**
 - ◆ Redundant DC Inputs
 - ◆ Hot swappable Fans for Front to Back Airflow SKU

Capacities

- Capable of up to 128 ONTs per GPON Interface

PON Standards Compliance

- GPON per ITU-T G.984
- Dynamic bandwidth allocation (DBA)
- Type B redundancy
- Rogue ONT detection

Subscriber Service Delivery

- Triple-play - voice, video, and data
- IGMP snooping and proxy with fast channel change
- DHCP relay
- PPPoE intermediate agent
- Proxy ARP
- In-service software upgrade

Layer 2 and Traffic Management

- 802.1q and 802.1ad VLAN manipulation, 802.1p CoS
- Hierarchical QoS and flexible scheduling
- Rate shaping per service
- TR-156 compliant user security

Network Timing

- Synchronous Ethernet
- IEEE 1588 PTP

Management

- Mosaic Cloud Platform
- NETCONF/YANG
- Remote Management through SSH
- Local Ethernet and USB Interfaces for Management
- OMCI to ONTs
- CLI
- In-service upgrade

GPON Optics

- Class B+ and Class C+ Compliant as specified in G984.2 Amendment 1 and 2
- 20 km Reach with 64x Split
- 30 km Reach with 32x Split
- 37 km Reach with 16x Split
- 62.5 km Extended Reach with 16x Split

Regulatory Standards

- FCC Part 15 Class A
- NEBS
- GR-1089 Core
- GR-63 Core
- CE marking
- EN60950-1
- RoHS 6 of 6

16-Port GPON OLT

Ordering Information

| Equipment | Part No. |
|---|------------|
| ADTRAN SDX 6010-16-port GPON OLT S2S | 11971305F1 |
| ADTRAN SDX 6010 16-port GPON OLT F2B | 11971305F2 |
| ADTRAN SFP GPON 2.5G 1.25G 30km | 1442530G1 |
| ADTRAN SFP GPON 2.5G / 1.25G C+ | 1442540F1 |
| Accessories | |
| SDX 6010-16 FAN MODULE S2S | 11971306F1 |
| SDX 6010-16 FAN MODULE F2B | 11971306F2 |
| SFP GPON OLT B+ optic 2.5G, 1.25G | 1442530G1 |
| SFP GPON OLT C+ optic 2.5G, 1.25G | 1442540F1 |
| 23-inch Rack Mount Kit | 11971307F1 |
| ETSI Rack Mount Kit | 11971308F1 |
| 19-inch Rack Mount Kit (Ships with the unit) | 11971309F1 |

ADTRAN

Pulse Supply
909 Ridgebrook Road., Sparks, Maryland 21152, USA
TEL : +1-410-583-1701 FAX : +1-410-583-1704



E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/adtran>

611971305F1-8E

September Copyright © 2019 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN® and the other trademarks listed at www.adtran.com/trademarks are registered trademarks of ADTRAN, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of ADTRAN items (e.g. commodities, technology, software), please visit www.adtran.com/exportlicense.



TL9000
TL 9000