



# Product Specifications

## Overview

- Type: EPON HGU (Home Gateway Unit)
- Part Name: 6304W (ubiQuoss)  
Part Name: C924WGB)
- Main Chip: BCM68380M+BCM43217T+BCM43602
- Downlink: 4x GE
- Operating Temperature: 0 - 40° C
- Operating Humidity: 10% - 90%, non-condensing
- Dimension: 247mm x 170mm x 35mm
- Installation: Wall mounting or desktop
- Weight: <500g
- Regulatory: Compliant with CE, UL/FCC (planned)

## Layer2 Bridging

- MAC
  - Support the Ethernet data frame filtering based on port, SA/DA
  - Support 2000byte MTU, compliant with IEEE 802.1ad
- VLAN
  - Support SSID to VLAN mapping
  - Support 802.1p, 802.1d, 802.1q based on QoS
  - Support ingress/egress 802.1p tag based QoS on each port
  - Support double tagging, compliant with IEEE 802.1ad

## Layer3 Routing

- Standard: RFC 2663, 3022, 3027, 3489
- IP
  - Support IPV4 & IPV6 dual stack
  - Support DHCP server/client & static IP address
- NAT/NAPT: Support NAT, NAPT, multi-NAT, transparent NAT
- DNS: Support DNS server, DNS relay, dynamic DNS
- Multicast: Support IGMP v2, v3, IGMP snooping
- Broadcast: Support broadcast storm suppression
- PPP
  - Support PPP associated with IETF RFCs 1332, 1333a, 1661, 1887e, 1994
  - Support PPP encapsulated over Ethernet
  - Support PPP pass through

## OAM, Security, Application

- Management: Support SNMP, TR-069, Web GUI, CLI
- Image:
  - Support firmware upgrade via remote server
  - Hold a working image & a alternative image for image rollback

- QoS:
  - Support classify packets based on DSCP, IP, protocol
  - Support classify packets based on 5 classification combination
  - Support SP, WRR, SP+WRR scheduler
- Restore Default:
  - Press a hidden button for more than 10s to restore factory default
  - Use GUI Web, CLI, Telnet method to restore factory default
- Security:
  - Support Access Control List
  - Support IP, MAC, port, URL filtering
  - Support ddos firewall
  - Support DMZ

## EPON Uplink

- Interface: 1x SC/APC connector, single mode fiber
  - Compliant with IEEE 802.3ah GEAPON
  - Compliant with FDA 21 CFR 1040.10 and 1040.11
  - Compliant with laser safety standard IEC-60825 Class 1

## Ethernet LAN

- Interface: 4x RJ45 connector
- Standard:
  - Compliant with IEEE 802.3, 802.3u, 802.3ab
  - Compliant with IEEE 802.3az, Green Ethernet
- Link:
  - Support Half-duplex & full-duplex operation
  - Support 10/100/1000Mbps auto-negotiation
  - Support MDI/MDIX auto detection

## WiFi

- Antenna:
  - Internal antennas
  - 4dBi@2.4GHz, 3dBi@5GHz
- Standard:
  - Compliant with IEEE 802.11n, 2.4GHz, 20/40MHz bandwidth
  - Compliant with IEEE 802.11AC, 5GHz, 20/40/80MHz bandwidth
  - Back compliant to 802.11b/g
- Speed
  - Wirespeed is 300Mbps, 2.4 GHz
  - Throughput > 140Mbps at 40MHz bandwidth
  - Wirespeed is 1200Mbps, 5GHz
  - Throughput > 600Mbps at 80MHz bandwidth
- WiFi Security
  - Support WPA, WPA2 authentication
  - Hardware accelerated AES-128 encryption/decryption, coupled with TKIP & IEEE 802.1x

- Support PBC or PIN WPS method
- SSID: Max 4 SSID

## FXS

- Interface: 2x RJ11 FXS port, each support up to 5 REN
- Standard: Support SIP, H.248, MGCP, SDP, RTP protocol
- CODEC: Support G.711, G.723, G.726, G.720(A/B) codec
- Call Service:
  - Support Call ID / Call waiting / Call forwarding / Call transfer / Call toggle / 3-way calling
  - Support T.38 FAX
- Feature:
  - Support echo cancellation, compliant with G.165, G.168
  - Support voice activity detection, comfort noise insertion

## USB

- Interface: 2x USB host port, type A
- Standard: USB 2.0, with 480Mbps wirespeed

## Power Solution

- Type: Wall adaptor + UPS (optional)
- Wall adaptor:
  - Input: 100VAC - 240VAC, 50/60Hz, Max 0.8A
  - Output: 12VDC, Max 2A
  - UL/FCC certified, US Type Plug
  - A standard barrel connector
- UPS:
  - 2x4 connector for external UPS
  - 12VDC out, 2A max
  - 4 alarm (on battery, battery failure, battery missing, battery low)

## Compliance

- Regulatory:
  - CE Compliant
  - UL/FCC (planned)
- EMC/EMI:
  - Compliant with EN 55022, class B
  - Compliant with EN 300 386
  - Compliant with EN 61000-4-1-5
- Safety:
  - Compliant with IP20 mechanical design
  - Support fire resistance material, compliant with UL94-V1, V0 is optional
  - Compliant with IEC 60950
- ENV kindness:
  - Compliant with RoHS standard
  - Compliant with WEEE standard
  - Compliant with energy efficiency level V

## Ordering Information

### Hardware Options

ADTRAN 6304W Residential Gateway ONU (power adaptor included)

### Part No.

1766304WF1



Pulse Supply  
909 Ridgebrook Road., Sparks, Maryland 21152, USA  
TEL : +1-410-583-1701 FAX : +1-410-583-1704



E-mail: sales@pulsesupply.com  
<https://www.pulsesupply.com/adtran>

### 61768001BF1-8A

January Copyright © 2017 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and Total Access are registered trademarks of ADTRAN, Inc. and its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit [www.adtran.com/warranty](http://www.adtran.com/warranty)

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)

