



TSU ACE



Low Cost T1/FT1 DSU/CSU

Product Features

- Single V.35 DTE interface
- Nx56 or Nx64 operation for data rates to 1.536 Mbps
- Auto and Manual D4(SF) or ESF framing support
- B8ZS or AMI line coding
- Easy to use front panel keypad for unit configuration
- Remote configuration from host TSU via FDL or 8k in-band
- Local and remote loop-back capability
- Extensive built in test capabilities
- IEC standard power connection
- Industry-leading five-year North American warranty

The ADTRAN® TSU ACE™ is a low cost, full-featured T1/FT1 Data Service/ Channel Service Unit (DSU/CSU). The TSU ACE provides an interface between T1 or Fractional T1 service and the end user's Data Terminal Equipment (DTE) for applications such as LAN-to-LAN bridging, Frame Relay circuit termination and video-conferencing. The TSU ACE provides access to traditional dedicated point-to-point T1 services as well as network termination for Frame Relay.


Housed in a compact, durable plastic housing the TSU ACE supports synchronous data rates from 56 kbps to 1.536 Mbps at Nx56 or Nx64 kbps. A single V.35 physical interface provides a connection to the end user's DTE equipment.

For configuration and testing, the TSU ACE provides the capability for remote control from a host TSU through the T1 FDL channel. If the FDL channel is unavailable, the host TSU can use 8 kbps of the data traffic to provide configuration and control of the remote TSU ACE. The in-band control channel is used on an as-needed basis and is automatically controlled by the host TSU.

The TSU ACE responds to standard local and remote loopback commands from the telephone company central office. In addition, the user has several built-in test capabilities including V.54 remote loopback and 511 BERT test patterns. Complete configuration and performance data is available from the front panel keypad and two-line by 16 character LCD display.

The ADTRAN TSU ACE desktop unit also provides integrated keyholes in the bottom housing for wall mount applications or can be rackmounted using ADTRAN's custom designed 19" shelves.

ADTRAN provides several T1 DSU/CSUs for a variety of customer applications. Additional products in the TSU family include the TSU LT™, TSU ESP™, TSU 100™, TSU 120™, TDU 120™ and the TSU 600™. These T1/FT1 DSU/CSUs offer flexibility, modularity and end user configuration. The modular approach allows the ADTRAN TSU family to serve in point to point T1 applications with a mixture of voice, data and video.



Low Cost T1/FT1 DSU/CSU

Product Specifications

Network Interface

Line Rate

- T1/FT1 (1.544 Mbps)

Physical Interface

- RJ48C: 8-Pin Modular

Framing

- SF/ESF
- Auto Detection

ESF Format

- AT&T 54016
- ANSI T1.403

Line Code

- AMI/B8ZS

Input Signal

- 0 to -36dB

DSO Assignment

- Contiguous
- Alternating

T1 Transmit Timing

- Network Loop Timed
- Internal
- DTE

DTE Interface

- **Bit Rate:** 56 Kbps to 1.536 Mbps, Nx56 or Nx64 Kbps (N=1 to 24)

Electrical

- CCITT V.35

Mechanical

- V.35 (Winchester Type 34 pin)

DTE Transmit Clock

- Automatic

Performance Monitor & Data

- BPVs/CRCs, ES, SES, UAS, % AS, % EFSEC, Alarms, Errors

Reports

- NI information stored for last 24 hours in 15 minute increments

PRMS

- ANSI Performance Report Messages (User selectable)

Tests

- **Local:** Payload/Line Loopback, DTE Loopback
- **Remote:** Payload/Line Loopback, V.54 (DTE) Loopback
- **Network:** CSU and DSU loopbacks

Built-In Test Patterns

- 511 (active DS0s) with error insert available
- 1:8 (all DS0s)
- All 1's (all DS0s)
- All 0's (all DS0s)

Remote Configuration

Required Software

- ADTRAN T-Watch Pro™

Required Hardware (one of the following)

- TSU LT (1203060L1)
- TSU (1200060L2)
- TSU RM (1202077L1)
- TSU ESP (1200169L1)

Agency Approvals

- FCC part 15, Class A, FCC Part 68, Industry Canada CS03, UL, CUL

Environment

- **Operating Temperature:** 0 to 50°C, (32 to 122°F)
- **Storage Temperature:** -20 to 70°C, (-4 to 158°F)
- **Relative Humidity:** Up to 95%, non-condensing

Physical

- **Dimensions:** 1.5" H, 6.25" D, 9" W
- **Weight:** 2 lbs
- **Power:** 115 VAC, 60Hz, 5W

Ordering Information

Equipment	Part #
TSU ACE	1202295L1
19" Rackmount Shelves	Part #
HRM-1MA Shelf - single unit	1200411L1
VRM-7MA Shelf - up to 7 units	1200417L1



Pulse Supply
909 Ridgebrook
Road., Sparks, Maryland 21152, USA
TEL : +1-410-583-1701
FAX : +1-410-583-1704

E-mail: sales@pulsesupply.c
https://www.pulsesupply.com/adtran



ADTRAN is an
ISO 9001: 2000 certified supplier.



ADTRAN is a
TL 9000 3.0 certified supplier.

61202295L1-8A March 2003
Copyright © 2004 ADTRAN, Inc.
All rights reserved.

Specifications subject to change without notice. TSU ACE, TSU LT, TSU ESP, TSU 100, TSU 120, TDU 120, TSU 600, and T-Watch PRO are trademarks of ADTRAN, Inc. ADTRAN is a registered trademark of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.