

| Antenna Type | Antenna Type | Gain (2.4GHz) | Gain (5GHz) | Horizontal Beamwidth | Vertical Beamwidth | Type of Connectors | No. of Units per AP | AP Compatibility | Use Case |
|-----------------------------------|--------------|---------------|-------------|----------------------|--------------------|--------------------|---------------------|------------------|--|
| M6060060MO1D3607O | Omni | 6 dBi | 6 dBi | 360° | 35°/25° | N-Style Plug | 1 | O-235E | Outdoor deployments including P2P links, Challenging indoor deployments such as warehouse, manufacturing environments. |
| M6060060P3D63607V | Directional | 6 dBi | 6 dBi | 80°/45° | 80°/45° | N-Style Plug | 1 | O-235E | Challenging Outdoor and indoor deployments such as stadiums, auditoriums, warehouse, manufacturing environments, especially where ceilings are high. |
| M060060M1D43607C | Omni | 5 dBi | 6 dBi | 360° | 45°/20° | N-Style Plug | 1 | O-105E | Outdoor deployments including P2P links, Challenging indoor deployments such as warehouse, manufacturing environments. |
| M6060060O23607O | Omni | 6 dBi | 6 dBi | 360° | 40° | N-Style Plug | 1 | O-105E | Outdoor deployments, Challenging indoor deployments such as warehouse, manufacturing environments. |
| M6060060P1D43607T | Directional | 6 dBi | 6 dBi | 105°/125° | 60°/70° | N-Style Plug | 1 | O-105E | Challenging outdoor and indoor deployments such as stadiums, warehouse, manufacturing environments, especially where ceilings are high. Recommended for sectoral pole/mast mounted deployments also. |
| M6080060DP33607 | Directional | 8 dBi | 6.5 dBi | 60°/65° | 65°/70° | N-Style Plug | 1 | O-105E | Challenging outdoor and indoor deployments such as stadiums, warehouse, manufacturing environments, especially where ceilings are high. Recommended for sectoral pole/mast mounted deployments also. |
| M602504O1D3620PV | Omni | 3 dBi | 4.5 dBi | 360° | 55°/60° | RPSMA Plug | 1 | C-230E, C-130E | Indoor deployments such as warehouse, manufacturing environments. |
| TWS244950-RPSMA-W | Omni | 3.5 dBi | 6 dBi | 360° | 70°/50° | RPSMA Plug | 6 | C-230E, C-130E | Rubber-ducky antenna which directly fits into the AP; suitable for wide variety for indoor deployments. |
| M040030D33620JB6 | Directional | 5 dBi | 6 dBi | 75° | 75° | RPSMA Plug | 1 | C-230E, C-130E | Low profile antenna for wall/ceiling mount for auditoriums and other dense indoor environments (blends into existing room décor for “out of sight” coverage and capacity) |
| TWPRO-WIFIANT-APM | Directional | 5 dBi | 6 dBi | 75° | 75° | RPSMA Plug | 1 | C-230E, C-130E | Antenna with rugged, RF-transparent IP-67-rated enclosure for protection against dust, water intrusion and strikes; ideal for challenging industrial applications such as manufacturing plants. |
| M6060060MO1D3620O | Omni | 6 dBi | 6 dBi | 360° | 35°/25° | RPSMA Plug | 1 | C-230E, C-130E | Chalenging indoor deployments such as stadiums, auditoriums, warehouse, manufacturing environments, especially where ceilings are high. |