

# Specifications



## Eaton BC350

120V 350VA 210W Standby UPS - 6 NEMA 5-15R Outlets, 50/60 Hz, 5-15P Plug, Desktop/Wall Mount

### General specifications

<b>PRODUCT NAME</b>	Eaton Tripp Lite series UPS
<b>CATALOG NUMBER</b>	BC350
<b>UPC</b>	037332210937
<b>PRODUCT LENGTH/DEPTH</b>	10.9 in
<b>PRODUCT HEIGHT</b>	7 in
<b>PRODUCT WIDTH</b>	5.5 in
<b>PRODUCT WEIGHT</b>	4.5 lb
<b>COMPLIANCES</b>	RoHS FCC Class A
<b>CERTIFICATIONS</b>	CSA certified UL 1778 NOM
<b>GLOBAL CATALOG</b>	BC350
<b>PRODUCT TYPE</b>	UPS



Powering Business Worldwide

## Product specifications

<b>TOPOLOGY</b>	Standby
<b>RACK SIZE</b>	0U
<b>VA RATING</b>	350 VA
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• BC350 120V 350VA 210W Standby UPS with 6 Outlets</li><li>• Owner's manual</li></ul>
<b>INPUT NOMINAL VOLTAGE</b>	120V AC
<b>NOMINAL FREQUENCY</b>	50/60 Hz
<b>INPUT FREQUENCY RANGE</b>	50/60 Hz
<b>RECEPTACLE</b>	5-15R
<b>OUTPUT NOMINAL VOLTAGE</b>	110 / 120V
<b>ELECTRIC CURRENT - MAX</b>	<ul style="list-style-type: none"><li>• 5A</li><li>• 5</li></ul>

**BATTERY REPLACEMENT**

IMPORTANT BATTERY REPLACEMENT INFORMATION > If your BC350 UPS has no battery access door, please contact a local electronics repair technician to source and install a matching replacement battery; If your BC350 UPS does have a battery replacement door and the original battery inside has a rating of 12V 2.8AH, please contact Tripp Lite for assistance

<b>BATTERY TYPE</b>	Valve Regulated Lead Acid (VRLA)
<b>RUNTIME AT HALF LOAD</b>	7 min
<b>RELATIVE HUMIDITY</b>	Up to 90% non-condensing
<b>INPUT PLUG TYPE</b>	NEMA 5-15P
<b>OUTPUT RECEPTACLES</b>	5-15R
<b>NOMINAL OUTPUT VOLTAGE</b>	110V 115V 120V
<b>NETWORK MANAGEMENT CARDS DETAILS</b>	Network management not supported
<b>PHASE (INPUT)</b>	Single-phase
<b>RUNTIME AT FULL</b>	2 min. (210W)

## Resources

<b>BROCHURES</b>	<a href="#">ENERGY STAR 2.0 Compliant UPS Systems in Colorado, Vermont and Washington State</a> <a href="#">Storm Season is Here Again Flyer (English)</a>
<b>MANUALS AND USER GUIDES</b>	<a href="#">Owner's Manual for Standby UPS Systems (Multi-language)</a>
<b>TECHNICAL DATA SHEETS</b>	<a href="#">Runtime Chart for BC350</a>

<b>LOAD</b>	
<b>COMMUNICATION INTERFACE</b>	None
<b>BATTERY ACCESS</b>	Includes bottom panel battery access door
<b>DC VOLTAGE</b>	12
<b>OPERATING TEMPERATURE RANGE</b>	32° to 104°F (0° to 40°C)
<b>OPTIONAL MOUNTING ACCESSORY NOTES</b>	Bottom panel keyhole mounting tabs enable wall-mount installation
<b>HIGH VOLTAGE TRANSFER TO BATTERY POWER</b>	145
<b>LOW VOLTAGE TRANSFER TO BATTERY POWER</b>	95
<b>APPLICATION</b>	<ul style="list-style-type: none"> <li>• Computer/Peripherals</li> <li>• Retail/Point of Sale</li> <li>• Hospitality</li> </ul>
<b>SWITCH CONFIGURATION</b>	Power switch enables UPS on / off control
<b>HOT SWAP PDU OPTIONS</b>	PDUB15 (2U / 8 5-15R outlets)
<b>AC SUPPRESSION JOULE RATING</b>	316
<b>HOUSING MATERIAL</b>	ABS
<b>OUTPUT AC WAVEFORM (AC MODE)</b>	Sine wave
<b>OUTPUT AC WAVEFORM (BATTERY MODE)</b>	PWM sine wave
<b>OUTPUT CAPACITY (KVA)</b>	0.35
<b>OUTPUT CAPACITY (WATTS)</b>	210
<b>PRIMARY UPS DEPTH (MM)</b>	185
<b>PRIMARY UPS HEIGHT (MM)</b>	105
<b>PRIMARY UPS WIDTH (MM)</b>	110
<b>AC SUPPRESSION RESPONSE TIME</b>	Instantaneous
<b>AUDIBLE ALARMS</b>	Alarm reports low-battery, fault, overload and replace battery conditions; Alarm remains silent during battery

	mode operation until low-battery status occurs; See manual for additional alarm notifications
<b>BATTERY START CAPABILITY</b>	Cold-start operation supported
<b>BATTERY REPLACEMENT DESCRIPTION</b>	Replaceable internal battery (see manual)
<b>LED INDICATORS</b>	Single green LED reports Line Power Mode (ON continuous), Battery Backup mode (flashes ON every 10 seconds); See manual for additional LED notifications
<b>FREQUENCY RATING DETAILS</b>	Auto-sensing
<b>OUTPUT VOLTAGE REGULATION (LINE MODE)</b>	120V ±20%
<b>OUTPUT VOLTAGE REGULATION(BATTERY MODE)</b>	120V ±10%
<b>RECOMMENDED ELECTRICAL SERVICE</b>	15A 120V
<b>STORAGE TEMPERATURE</b>	5° to 122°F (-15° to 45°C)
<b>MAXIMUM INPUT AMPS</b>	5
<b>UPS INPUT CORD LENGTH (M)</b>	1.5
<b>UPS POWER MODULE DIMENSIONS</b>	4.13 x 4.33 x 7.28
<b>POWER MODE TRANSFER TIME</b>	6 milliseconds typical (10 milliseconds max)
<b>TOTAL OUTLETS</b>	6
<b>OUTPUT CAPACITY (VA)</b>	350
<b>CONNECTED EQUIPMENT INSURANCE</b>	\$100,000 Ultimate Lifetime Insurance
<b>EMI AC NOISE SUPPRESSION</b>	EMI / RFI AC Noise Suppression
<b>UPS INPUT CONNECTION TYPE</b>	5-15P
<b>GREEN ENERGY-SAVING FEATURES</b>	Greater than 95% efficiency - GREEN UPS
<b>UPS OUTPUT RECEPTACLES</b>	3 UPS outlets, 3 surge-only outlets
<b>HIGH AVAILABILITY UPS FEATURES</b>	Surge/noise protection

<b>NOMINAL INPUT VOLTAGE SUPPORTED</b>	120V AC
--	---------

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



Pulse Supply  
909 Ridgebrook Road., Sparks, Maryland 21152, USA  
TEL : +1-410-583-1701 FAX : +1-410-583-1704  
E-mail: sales@pulsesupply.com  
<https://www.pulsesupply.com/eaton>