

Specifications

Eaton INTERNET750U

750VA 450W Standby UPS - 12 NEMA 5-15R Outlets, 120V, 50/60 Hz, USB, 5-15P Plug, Desktop / Wall Mount



General specifications

PRODUCT NAME	Eaton Tripp Lite series UPS
CATALOG NUMBER	INTERNET750U
UPC	037332211088
PRODUCT LENGTH/DEPTH	14.92 in
PRODUCT HEIGHT	7.83 in
PRODUCT WIDTH	5.98 in
PRODUCT WEIGHT	8.14 lb
COMPLIANCES	ENERGY STAR certified FCC Class B RoHS
CERTIFICATIONS	NOM UL 1778 RETIE CSA certified
GLOBAL CATALOG	INTERNET750U
PRODUCT TYPE	UPS



Powering Business Worldwide

Product specifications

TOPOLOGY	Standby
RACK SIZE	0U
VA RATING	750 VA
PACKAGE CONTENTS	<ul style="list-style-type: none">• INTERNET750U 750VA 450W 120V Standby UPS with 12 Outlets• USB cable• Owner's manual
INPUT NOMINAL VOLTAGE	120V AC
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	50/60 Hz
RECEPTACLE	5-15R
OUTPUT NOMINAL VOLTAGE	110 / 120V
ELECTRIC CURRENT - MAX	<ul style="list-style-type: none">• 10A• 10
BATTERY REPLACEMENT	RBC51
BATTERY TYPE	Valve Regulated Lead Acid (VRLA)
RUNTIME AT HALF LOAD	8.6 min
RELATIVE HUMIDITY	0-90% non-condensing
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
POWERALERT SOFTWARE	For local monitoring via the UPS's built-in USB port, download PowerAlert software at https://tripplite.eaton.com/products/power-alert
NOMINAL OUTPUT VOLTAGE	110V 115V 120V
NETWORK MANAGEMENT CARDS DETAILS	Network management not supported
OUTPUT POWER FACTOR	0.6
PHASE (INPUT)	Single-phase
RUNTIME AT FULL LOAD	2 min. (450W)
COMMUNICATION INTERFACE	USB (HID enabled) USB interface cable included
BATTERY ACCESS	Battery access door
DC VOLTAGE	12

OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
COMMUNICATIONS CABLE	USB interface cable included
INPUT CIRCUIT BREAKERS	10A
HIGH VOLTAGE TRANSFER TO BATTERY POWER	145
LOW VOLTAGE TRANSFER TO BATTERY POWER	95
APPLICATION	<ul style="list-style-type: none"> • Computer/Peripherals • Audio/Video • Retail/Point of Sale • Hospitality
SWITCH CONFIGURATION	Switch controls power off/on status
HOT SWAP PDU OPTIONS	PDUB15 (2U / 8 5-15R outlets)
AC SUPPRESSION JOULE RATING	316
HOUSING MATERIAL	ABS
OUTPUT AC WAVEFORM (AC MODE)	Pure sine wave
OUTPUT AC WAVEFORM (BATTERY MODE)	PWM sine wave
OUTPUT CAPACITY (KVA)	0.75
OUTPUT CAPACITY (WATTS)	450
OUTPUT CAPACITY DETAILS	6.3A @ 120V. 110%±10%,GOES TO FAULT AFTER 5MIN; 120%±10%,GOES TO FAULT IMMEDIATELY 110%±10%,SHUTS DOWN IN 5 SEC; 120%±10%, SHUTS DOWN IMMEDIATELY
OPERATING ELEVATION	Up to 3000m
PRIMARY UPS DEPTH (MM)	310
PRIMARY UPS HEIGHT (MM)	85
PRIMARY UPS WIDTH (MM)	130
AC SUPPRESSION RESPONSE TIME	Instantaneous
AUDIBLE ALARMS	UPS remains silent in battery backup mode; Alarm sounds only to report low-battery,

	fault, overload and replace-battery conditions
BATTERY START CAPABILITY	Cold-start operation supported
BATTERY REPLACEMENT DESCRIPTION	Replaceable internal battery. Contact customer support for assistance.
LED INDICATORS	Set of 3 status LEDs indicate operating mode, low-battery, overload, replace-battery and fault conditions
FREQUENCY RATING DETAILS	Output is regulated to +/-0.05Hz when input frequency exceeds +/-5Hz of nominal.
OUTPUT VOLTAGE REGULATION (LINE MODE)	120V (±20%)
OUTPUT VOLTAGE REGULATION(BATTERY MODE)	120V (±10%)
RECHARGEABLE BATTERY	8 hours (10% to 90%)
RECOMMENDED ELECTRICAL SERVICE	15A 120V
STORAGE TEMPERATURE	5° to 113°F (-15° to 45°C)
NOMINAL VOLTAGE DETAILS	120V sinusoidal in line mode and 120V PWM in battery mode
VOLTAGE REGULATION DESCRIPTION	Input voltage range of 95 to 145V
WATCHDOG COMPATIBILITY	Supports Watchdog application, OS and hard-reboot restart options for remote applications
MAXIMUM INPUT AMPS	10
UPS INPUT CORD LENGTH (M)	1.5
UPS POWER MODULE DIMENSIONS	3.35 x 5.12 x 12.2
POWER MODE TRANSFER TIME	6 milliseconds typical (10 milliseconds max)
TOTAL OUTLETS	12
OUTPUT CAPACITY (VA)	750
CONNECTED EQUIPMENT INSURANCE	\$100,000 Ultimate Lifetime Insurance
EMI AC NOISE SUPPRESSION	EMI / RFI AC Noise Suppression
UPS INPUT CONNECTION TYPE	5-15P
GREEN ENERGY-	Greater than 95% efficiency - GREEN UPS

SAVING FEATURES	
UPS DATALINE SUPPRESSION	1 line TEL/DSL or Ethernet
UPS OUTPUT RECEPTACLES	6 UPS outlets, 6 surge-only outlets
HIGH AVAILABILITY UPS FEATURES	Surge/noise protection
NOMINAL INPUT VOLTAGE SUPPORTED	120V AC

Resources

BROCHURES [Storm Season is Here Again Flyer \(English\)](#)

[Integrated Solutions Brochure \(English\)](#)

MANUALS AND USER GUIDES [Owner's Manual for UPS Systems \(Multi-language\)](#)

TECHNICAL DATA SHEETS [Runtime Chart for INTERNET750U](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Pulse Supply
 909 Ridgebrook Road., Sparks, Maryland 21152, USA
 TEL : +1-410-583-1701 FAX : +1-410-583-1704
 E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/eaton>