



The Luxriot DVR Hybrid Capture Boards are designed to work with Luxriot EVO S and Global Server Software to capture & record Analog Video Streams



Capture Devices

LUXRIOT HYBRID BOARDS

Features:

- Full or Low Profile*
- Realtime 30fps Per Channel
- Hardware Motion Detection
- Audio and Video on All Channels*
- H.264 Compression
- 32 & 64 Bit Windows Drivers
- NTSC/PAL
- Up to 1080p Resolution for HDCCTV SDI Board.
- Up to D1 Resolution for Standard Boards.

Optimized & Designed for:





• Luxriot Models

Luxriot Hybrid Capture Board Models					
HC7008	HC7008L	HC7016	HC7016L		
HC7032	HC7004HD				

L is for Low Profile

• Specifications

Boards	HC7008*	HC7016*	HC7032	HC7004HD (HDCCTV)	
Power Input	None SATA Power				
Form Factor	PCI-E X1				
Total FPS	240	480	960	120	
Compression	H.264				
Resolutions	Up to D1			Up to 1080p	
Drivers	Windows 32 Bit and 64 Bit				
Formats	NTSC/PAL				
Boards Per Machine	4	4	4	4	
Video Inputs	8	16	32	4	
Audio Inputs	8	16	32	4	
Motion Detection	On Board				
Video Outs	2			0	

* Full or Low Profile

Distributed By: Pulse Supply Tel: +1-410-583-1701 Email: sales@pulsesupply.com www.pulsesupply.com/luxriot





• Luxriot Boards Detailed





HC7032



HC7008L



HC7016L



HC7004HD



Distributed By: Pulse Supply Tel: +1-410-583-1701 Email: sales@pulsesupply.com www.pulsesupply.com/luxriot

